



star DP8340

Versatile, Wide, Mobile Compact Receipt Printer



The DP8340 is a unique 114mm wide dot matrix impact printer used all around the world in multiple applications. The wide width allows it to print reports, receipts or invoices depending on your needs. Its ability to be powered by 12V in addition to its high reliability, make it a perfect product for mobile applications in vehicles. Special items on the receipt can be easily identified due to the printers red print feature.

Visit www.starmicronics.com.au to learn more.

Typical Applications

- Receipt Printer
- Mobile Printing
- Data Terminals
- Test Equipment Results
- Weights and Measures (Scale)

Product Range

- DP8340FC Tear Bar, Parallel, 4.5" Paper Width
- DP8340FM Tear Bar, RJ-45 Serial, 4.5" Paper Width
- DP8340RC Tear Bar, Parallel, 3.25" Paper Width
- DP8340RM Tear Bar, RJ-45 Serial, 32.5" Paper Width
- DP8340SC Tear Bar, Parallel, 4.5" Paper Width, Sprocket Version
- DP8340SM Tear Bar, RJ-45 Serial, 4.5" Paper Width, Sprocket Version




Hospitality



Kitchen



Wide Format



Black & Red Printing



DP8340 Specifications

		The Original Ultra Reliable POS Printer!	
Features	Hardware Ultra Reliable Receipt Printer 2 LPS (Lines per Second) Small Footprint Wide Format 4.5" Model Standard 3.25" Model Sprocket Model	40 / 60 Column 9-Pin Print Head 12 VDC (Ideal for Mobile Applications)	
Connectivity	RJ-45 Serial 25-Pin Serial Parallel USB Powered USB Ethernet Wireless LAN Dual 9-Pin Serial/USB	Virtual Serial Port to USB Virtual Serial Port to Ethernet Virtual TCP/IP Port	
Note: Connections in bold are supported; grayed-out connection types may be supported by special request.			
Drivers	Windows® XP Vista (32 bit) Windows 7 (32 bit) Server 2008 (32 bit) CE XP Embedded POS for .NET	OPOS™ JavaPOS™ StarIO SDK	
What's Included	User Manual Paper Holders Re-Roll Prevention Guard Ribbon Cartridge DIP Switch Cover		
Optional Accessories	External Power Supply (PS8340) Automotive 12V Power Adapter	Ribbons: SF-01B – Black SF-03BR – Black/Red	
Models	DP8340FM RJ-45 Modular Jack Serial I/F, 4.5" Roll Paper DP8340RM RJ-45 Modular Jack Serial I/F, 3.25" Roll Paper DP8340FC Parallel I/F, 4.5" Roll Paper DP8340RC Parallel I/F, 3.25" Roll Paper DP8340SM RJ-45 Modular Jack Serial I/F, 4.5" Sprocket Paper DP8340SC Parallel I/F, 4.5" Sprocket Paper		
Technical Specifications	Print Method : 9 Pin Impact Dot Matrix Print Speed : 2 LPS (Lines per Second) Paper Width : 82.5mm to 114.3mm Paper Thickness : 0.07 - 0.09mm Paper Diameter : Max 80mm Emulation : Star DP8340	Power: 12VDC MCBF: 10 Million Lines Dimensions: W=202mm, H=98mm, D=200mm	
Warranty	1-Year Limited Warranty		
For Further Information	Sales: (02) 8788 1500 Technical Support: (02) 8788 1547	Web: http://www.starmicronics.com.au	

11/9/11

