



**GC Weighing
& Calibrations**
don't weight to call

**FS-KI SERIES WET AREA IP65
CHECKWEIGHING SCALES**

SCALES



GC WEIGHING & CALIBRATIONS

**Unit 7 No 8 - 10 Christensen Road
Stapylton - QLD 4207**

sales@gcweigh.com.au





**GC Weighing
& Calibrations**
don't weight to call

**FS-KI SERIES WET AREA IP65
CHECKWEIGHING SCALES**

SCALES

- **Ultra Fast Weighing- Stability in 0.5 seconds**
- **Trade approved by NMI Australia**
- **IP65 Dustproof & Waterproof**
- **Comparator Function- Pack to preset targets**
- **Large Indicator Lights- Displays a HI LO or GO result against your targets**
- **Analog Sweep Display (ASD)- Ideal for target filling with a fast flowing product**
- **Backlight Function- Perfect for poorly lit work areas**



GC WEIGHING & CALIBRATIONS

**Unit 7 No 8 - 10 Christensen Road
Stapylton - QLD 4207**

sales@gcweigh.com.au





Why These Large and Bright Comparator Lights Guarantee You Maximum Productivity

Do you know how fast humans can process visual information? Research shows we usually need just a tiny fraction of a second to tell one image from another. As the speed of check weighing is a critical requirement in today's food industry, A&D's FS-i Series takes full advantage of human visual ability by means of vivid tricolor lights, in addition to its ultra-fast, 0.5-second weighing performance.



High-speed Weighing and Data Acquisition

Stabilization takes only 0.5 seconds, realizing extremely efficient weighing. This becomes even more significant when coupled with a refresh rate of 20 times/second, which allows fast data acquisition via the optional serial interface (FS-03i or FS-04i).

Simple and Error-free Comparator Judgment

The highly distinct LED lights are an excellent guide for anyone to perform fast and adequate product packaging. The sound of the buzzer function can also aid in making correct judgments.

NEW! Auto-tare Function

To save you from the burden of pressing the TARE key in consecutive measurements, the scale can perform tare automatically each time the weight reaches the target range.

NEW! Negative Comparison

You can now compare negative values by removing weights from the scale.

Take-away Check Weighing

By using the auto-tare and negative comparison functions together, it is possible to perform "take-away" check weighing. This is very convenient when measuring out the same amounts from a container.



Tare the initial weight (either manual or automatic).

Take out the content for the

The scale performs tare automatically and returns the display to zero.

Please also visit our video library at

to see it in action



Large Memory for Comparator Settings

The scale stores up to 100 sets of comparator limits, which saves you a lot of trouble if you need to change the setting frequently.

Error Prevention by Simplified Operation Mode

In simplified operation mode, operators are limited to the minimum required keys to avoid accidental changes to the scale settings. As with the comparator lights, this will ensure simple, efficient, and accurate work.

Stainless Steel and IP65 Water & Dustproof Construction

The scale is easy to wash and keep hygienic. Its epoxy-coated load cell has also proven highly reliable under harsh environments.



Analog Sweep Display for Intuitive Filling Control

A 60-segment horizontal bar graphically shows you the weight value in relation to the full capacity, target weight, or upper/lower limits.



Example of target weighing display mode

Sealed Lead Acid Rechargeable Battery (Optional)

You can operate the scale with the optional rechargeable battery (up to approx. 80 hours) where an AC power supply is not present or when it is unstable.

Serial Data and Comparator Relay Outputs (Optional)

RS-232C + relay (FS-03i) and RS-422/485 + relay (FS-04i) interfaces are available for outputting data to external devices or controlling multiple FS-i scales.

Other Features

- ✓ LCD with backlight for better visibility in dark areas
- ✓ Easy numerical entry using the 10-key pad
- ✓ Pre-set tare function to deduct known tare weights
- ✓ Three weighing resolutions: 1/3,000, 1/6,000 (or 1/7,500), and 1/12,000 (or 1/15,000)*
- ✓ Five units of weighing available (kg, g, lb, oz, and lb-oz)
- ✓ NSF-certified for sanitation in food industry
- ✓ Universal Flexi Coms (UFC) function, which enables free editing of printout format



FS-D – Indicator for Check Weighing Scales

At last, the solution for those who liked the features and functions of the FS-i display unit but wanted to use a different scale platform. The FS-D, which comes with a desktop/wall-mount stand and a connector plug, can even be used with platforms other than A&D's. The eight preset capacities range from 6 kg (15 lb) to 1,500 kg (3,500 lb) and the three resolutions from 1/3,000 to 1/12,000 (or 1/15,000)*.

*Only one of each can be selected at a time.



SB-6K13SW (sold separately)

Now Available!